

# HYGROPALM HP32



HC2A probe

## BENEFITS

- Relative humidity, temperature and psychrometric calculations
- Graphical display for graphs and up to 4 values
- Freely settable visual and audible alarms on every value
- 64,000 data points memory with programmable logging interval
- Long-life rechargeable battery (up to 48 hours at a logging interval of 30 seconds)

## APPLICATIONS

- Field inspection and spot checks in HVAC
- Building management systems
- Agriculture and food industry
- Pharmaceutical industry



## TECHNICAL INFORMATION


### Compatible with

- All HC2 and HC2A probes
- HW4 software > V3.9

### Package content

- HygroPalm HP32 (without probe)
- Soft case
- Micro-USB cable (computer connection and battery charging)
- HW4 LITE license key (max. 3 instruments connected)

### Drawing



General specifications	
Device type	Handheld device (%RH / °C)
Compatible probes	All HC2A and HC2 probes
Application range	-10...60 °C   0...100 %RH (non-cond.)
Storage range	-10...45 °C   10...90 %RH
Probe application range	Depends on the probe
Accuracy	Depends on the probe
Functions	Spot measurements Programmable logging interval MIN / MAX / AVG
Logging interval	1 s...24 h
Memory capacity	8 x 8000 data points
Psychrometric calculations	Dew / Frost point (Dp / Fp) Wet bulb temperature (Tw) Enthalpy (H) Vapor concentration (Dv) Specific humidity (Q) Mixing ratio by weight (R) Vapor pressure (E) Saturation vapor pressure (Ew) Saturation vapor density (SVD)
Calculation method	WMO Standard
Display refresh rate	1 s (typical)
Integrated battery	Lithium polymer, 3.7 V, 1000 mAh 48 h – Logging every 30 s, screen off 10 h – Screen always on
PC interface	Micro-USB port, HW4 compatible > V3.9
Housing / Mechanics	
Enclosure material	ABS, TPR
IP protection class	IP65
Dimensions	160 x 63 x 30 mm
Weight	185 g

Subject to technical change without notice. Printing and other errors reserved.

59073E/2018-12

# POSSIBLE PROBES FOR THE HP32

## STANDARD AND HIGH PRECISION PROBES

Accuracy (Standard):	$\pm 0.8\% \text{RH}$ , $\pm 0.1 \text{ K}$ at $10\ldots 30\text{ }^{\circ}\text{C}$
Accuracy (High Precision):	$\pm 0.5\% \text{RH}$ at $10\ldots 90\% \text{RH}$ , $\pm 0.1 \text{ K}$ at $10\ldots 30\text{ }^{\circ}\text{C}$
Application range:	$-50\ldots 100\text{ }^{\circ}\text{C}$ , $0\ldots 100\% \text{RH}$
Long-term stability:	$< 1\% \text{RH} / \text{year}$
Order code:	HC2A-S (Standard) HC2A-SH (High Precision)



## HIGH TEMPERATURE HANDHELD PROBE

Accuracy:	$\pm 0.8\% \text{RH}$ , $\pm 0.2 \text{ K}$ at $10\ldots 30\text{ }^{\circ}\text{C}$
Application range:	$-100\ldots 200\text{ }^{\circ}\text{C}$ , $0\ldots 100\% \text{RH}$
Long-term stability:	$< 1\% \text{RH} / \text{year}$
Cable length:	2 m
Order code:	HC2-HK25



## INSERTION PROBES

Accuracy:	$\pm 0.8/1.5\% \text{RH}$ , $\pm 0.1/0.3 \text{ K}$ at $10\ldots 30\text{ }^{\circ}\text{C}$
Application range:	$-40\ldots 85\text{ }^{\circ}\text{C}$ / $0\ldots 100\% \text{RH}$
Long-term stability:	$< 1\% \text{RH} / \text{year}$
Cable length:	2 m
Order code:	HC2-P05, HC2-P28, HC2-P50



# HP32 PRODUCT SETS

## HP32-S-SET

### Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe

Order code: HP32-S-SET



## HP32-SET

### Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe
- 1x E2-02A extension cable 2 m
- 1x ER-15 calibration device
- 1x EA35-SCS humidity standard SCS

Order code: HP32-SET



## HP32-A-REF-SET

### Consisting of:

- 1x HP32 handheld instrument
- 1x HC2A-S Standard probe with 1x SCS-1T-3H
- 1x E2-02A extension cable 2 m

Order code: HP32-A-REF-SET



## POSSIBLE SOFTWARE FOR THE HP32

### HW4 LITE

- Free license included with the device
- Visualization, data export and evaluation of measured values
- **A maximum of 3 instruments can be connected simultaneously**

Order code: HW4-LITE

### HW4-STANDARD

- Single-user application license
- Visualization of multiple loggers and measured values
- Monitoring (one instrument at a time), data logger programming, data retrieval, scaling, instrument settings, alarm function, service and configuration tool for Rotronic instruments, time synchronization, adjustment and calibration of Rotronic probes
- No password protection

Order code: HW4-E-V3

### HW4-PROFESSIONAL (HW4-P-V3)

- Network applications in the pharmaceutical and food industries
- All functions of the Standard edition
- Multiple-user applications license (same site)
- Fulfills the requirements for electronic data records and signatures (FDA21 CFR Part 11, Annex 11)
- Grouping of devices, graph overlays, printing of reports

Order code: HW4-P-V3

An up-to-date overview of our extensive range of accessories such as probes, cables, filters, sets, software and calibration equipment compatible with the HygroPalm HP32 is available on our web site: [www.rotronic.com](http://www.rotronic.com).