

HIGH PERFORMANCE WHITE LITHIUM GREASE



PRODUCT OVERVIEW

WD-40 Specialist High Performance White Lithium Grease is a thicker solution which provides long term lubrication that won't drip nor run. It's great for metal to metal applications, reducing friction to ensure your tools and equipment keep moving smoothly. This product can be used on load bearing metal connections.

FEATURES AND BENEFITS

- ⊕ For use on metal to metal connections
- ⊕ Water and heat resistant lubricant
- ⊕ Long last protection against rust and corrosion
- ⊕ Ideal for load bearing application
- ⊕ High viscosity lubricant
- ⊕ Withstands temperatures of -18°C to +145°C

NSF H2 Registered #145376



NARROW SPRAY



WIDE SPRAY

TYPICAL APPLICATIONS

Motor pivot points, Bearings, Winches, Latches, Pistons, Conveyors, Overhead Door Tracks, Cables, Bearings, Runners, Water Pumps, Gear & Brake Mechanisms, Metal parts, Hinges, Catches.

DIRECTIONS FOR USE

Shake can well. Apply by spraying directly on surface to be lubricated and protected.

TECHNICAL DATA

PROPERTY	HIGH PERFORMANCE SILICONE LUBRICANT
Appearance	Off- White
Odour	pleasant lemon odour
SG	0.84 - 0.86
Temperature range	Effective performance at temperatures from -18°C to +145°C
Solubility	Not miscible with water
NSF category	H2
Flammability	Classed as extremely flammable under current legislation
Compatibility	Ideal for metal-to-metal application
Lubrication ASTM D-4172	Scar depth 0.41 mm
Extreme pressure lubrication ASTM 3233	1151 lb
Corrosion protection ASTM B-117	0 at 72h

PACKAGING SPECIFICATIONS

PRODUCT NUMBER	UNIT SIZE	CASE SIZE
44390	400ml	400ml x 12

